


# Radiator Caps Catalogue


A close-up photograph of a radiator cap. The cap is dark blue or black with a silver-colored top. The top has a circular opening with a green seal. The cap is shown in a slightly open position, revealing a bright green liquid (coolant) inside. The background is dark and out of focus, showing other parts of the engine or radiator assembly.


# CONTENTS

Case-IH .....	3
Claas .....	5
David Brown .....	6
Deutz-Fahr .....	7
Fendt .....	8
Fiat .....	9
Ford .....	10
FTP .....	12
Hurlimann .....	13
Iveco .....	14
John Deere .....	15
Lamborghini .....	17
Landini .....	18
Leyland .....	19
Massey Ferguson .....	20
McCormick .....	22
New Holland .....	23
Perkins .....	25
SAME .....	26
Sisu .....	27
Standard (Hotchkiss) .....	28
Steyr .....	29
Ursus .....	30
Valtra-Valmet .....	31
Zetor .....	33


# Case-IH

<b>KR-3134146R1N</b>	OEM: 3134146R1
Max. Working Pressure: 0.8 BAR	
Pressure (PSI): 11.6 PSI	<b>Fitment Information:</b> Engine D111, D155, D179, D206, D239, D268, D310, D358, DT239, DT358, DT402 Tractor 323, 353, 383, 423, 433, 440, 453, 523, 533, 540, 553, 633, 640, 644, 645, 654, 724, 733, 734, 740, 743, 744, 745, 745S, 824, 833, 834, 840, 844, 844S, 844XL, 845, 856, 940, 946, 955, 956, 1046, 1055, 1056, 1246, 1255, 1455
Inside Diameter: 38 mm	
Working Diameter: 55 mm	
	


<b>KR-3475308M1N</b>	OEM:
Max. Working Pressure: 0.5 BAR	
Pressure (PSI): 7 PSI	<b>Fitment Information:</b> CS63, 68, 75, 78, 86, 94, CVX120, 130, 150, 170, JX55, 60, 65, 70, 80, 85, 90, 95, 100, JX1060, 1070, 1075, 1080, 1085, 1090, 1095, 1100, VJ60, 70, 80
Inside Diameter:	
Working Diameter:	
	


<b>KR-4274034</b>	OEM: 4274034
Max. Working Pressure:	
Pressure (PSI):	<b>Fitment Information:</b> FARMALL JX70, 75, 80, 90, 100, 110, JX70U, 80U, 90U, 100U, JX1060C, 1070C/U, 1075C, 1080U, 1085C, 1090U, 1095C, 1100U, JXU75, 85, 95, 105, 115, QUANTUM 65, 75, 85, 95
Inside Diameter:	
Working Diameter:	
	

<b>KR-81747955N</b>	OEM:
Max. Working Pressure: 0.8 BAR	
Pressure (PSI): 11.6 PSI	<b>Fitment Information:</b> 383, 423, 433, 440, 453, 533, 540, 553, 633, 640, 644, 654, 724, 733, 740, 743, 744, 745, 745S, 824, 833, 840, 844, 844S, 845, 856, 940, 946, 955, 956, 995, 1046, 1055, 1056, 1246, 1255, 1455, AVJ55, 60, 70, CS110, 120, 130, 150, CVX120, 130, 150, 170, JX55, 60, 65, 70, 80, 85, 90, 95, 100, JX1060, 1070, 1075, 1080, 1085, 1090, 1095, 1100, VJ60, 70, 80
Inside Diameter: 36.5mm	
Working Diameter: 55mm	
	


<b>KR-83957211N</b>	OEM:
Max. Working Pressure: 0.9 BAR	
Pressure (PSI): 13 PSI	<b>Fitment Information:</b> Tractor 225, 250, 280, 310, 335, 5120, 5130, 5140, 5150, 7110, 7120, 7130, 7140, 7210, 7220, 7230, 7240, 7250, C80, 90, CX50, 60, 70, 80, 90, 100, MX80C, 90C, 100C, MX100, 110, 120, 135, 150, 170, 180, 200, 210, 220, 230, 240, 255, 270, 285, MXM175, 190, QUADTRAC 370, 400, 450, 470, 500, 540, 550, 580, 600, 620, STEIGER 335, 370, 385, 420, 435, 470, 485, 500, 535, 540, 580, 620, STX280, 330, 380, 430, 480, 530
Inside Diameter:	
Working Diameter:	
	

<b>KR-AL56759N</b>	OEM:
Max. Working Pressure: 0.6 BAR	
Pressure (PSI):	<b>Fitment Information:</b> 383, 423, 433, 440, 453, 533, 540, 553, 633, 640, 644, 654, 724, 733, 740, 743, 744, 745, 745S, 824, 833, 840, 844, 844S, 845, 856, 940, 946, 955, 956, 995, 1046, 1055, 1056, 1194, 1246, 1255, 1294, 1394, 1455, 1494, 1594, 1694, AVJ55, 60, 70, JX55, 60, 65, 70, 80, 85, 90, 95, 100, JX1060, 1070, 1075, 1080, 1085, 1090, 1095, 1100, VJ60, 70, 80
Inside Diameter: 38mm	
Working Diameter: 54mm	
	


<b>KR-VPE3200</b>	OEM: 80889R91, E81942, K945362
Max. Working Pressure: 0.5 BAR	
Pressure (PSI): 7 PSI	<b>Fitment Information:</b> 1194, 1294, 1394, 1494, 1594, 1694
Inside Diameter: 38mm	
Working Diameter: 54mm	
	

<b>KR-VPE3218</b>	OEM: 3111424R91, 707338R91
Max. Working Pressure: 0.5 BAR	
Pressure (PSI): 7 PSI	<b>Fitment Information:</b> Engine BD144, BD154 Tractor 250, 275, 276, 354, 374, 384, 414, 434, 444
Inside Diameter:	
Working Diameter:	
	


<b>KR-VPE3220</b>	OEM: 83935905
Max. Working Pressure: 0.9 BAR	
Pressure (PSI): 13 PSI	<b>Fitment Information:</b>
Inside Diameter:	FARMALL JX75, JX55, 60, 65, 70, 75,
Working Diameter:	80, 85, 90, 95
	

<b>KR-VPE3228</b>	OEM: 4999682
Max. Working Pressure: 0.7 BAR	
Pressure (PSI): 10 PSI	<b>Fitment Information:</b>
Inside Diameter:	AVJ55, 60, 70, FARMALL JX75, JX55,
Working Diameter:	60, 65, 70, 80, 85, 90, 95, 100, JX1060,
	
	1070, 1075, 1080, 1085, 1090, 1095, 1100

# Claas


<b>KR-4999682N</b>	OEM:
Max. Working Pressure: 0.7 BAR	
Pressure (PSI): 10 PSI	<b>Fitment Information:</b>
Inside Diameter:	Combine Harvester COMMANDOR 114, 115, 228-116, DOMINATOR 38, 48, 58-48, 68, 76, 78, 86, 88, 96, 98, 106, 118-108, 128-108, 150-130, LEXION 410-405, 430-410, 430-415, 460-440, 460-450 TERRA TRAC, 470, 480, 480 TERRA TRAC, 560-540, 570, 580, 600, MEDION 330-310, 340, MEGA 202, 204-203, 218-218, 350, Disc Mower COUGAR 1400, Tractor XERION 2500, 3000
Working Diameter:	
	


<b>KR-AL76661N</b>	OEM: 6005018131
Max. Working Pressure: 0.9 BAR	
Pressure (PSI): 13 PSI	<b>Fitment Information:</b>
Inside Diameter:	ARES 610, 620, 630, 640
Working Diameter:	
	

<b>KR-VPE3253</b>	OEM: 6005018131
Max. Working Pressure: 0.9 BAR	
Pressure (PSI): 13 PSI	<b>Fitment Information:</b>
Inside Diameter:	ARES 610, 620, 630, 640
Working Diameter:	
	


<b>KR-VPE3259</b>	OEM: 0021935750
Max. Working Pressure: 1.1 BAR	
Pressure (PSI): 16 PSI	<b>Fitment Information:</b>
Inside Diameter:	ARION 410, 420, 430, 440, 450, 460, 510, 520, 530, 540, 610, 620, 630, 640, AXION 810, 820, 830, 840, 850
Working Diameter:	
	


<b>KR-VPE3260</b>	OEM: 6005029044
Max. Working Pressure: 0.8 BAR	
Pressure (PSI): 11.6 PSI	<b>Fitment Information:</b>
Inside Diameter:	CELTIS 426, 436, 446, 456
Working Diameter:	
	


<b>KR-VPE3261</b>	OEM: 6005031348
Max. Working Pressure: 0.9 BAR	
Pressure (PSI): 13 PSI	<b>Fitment Information:</b>
Inside Diameter:	NECTIS 217, 227, 237, 247, 257, 267
Working Diameter:	
	

<b>KR-VPE3262</b>	OEM: 7700066199
Max. Working Pressure: 0.8 BAR	
Pressure (PSI): 11.6 PSI	<b>Fitment Information:</b>
Inside Diameter:	ARES 616, 617, 630, 640, 656, 657, 696, 697, 710, 720, 725, 735, 815, 816, 825, 826, 836, ATLES 915, 926, 936, 946
Working Diameter:	
	


# David Brown


<b>KR-3475308M1N</b>	OEM:
Max. Working Pressure: 0.5 BAR	
Pressure (PSI): 7 PSI	<b>Fitment Information:</b>
Inside Diameter:	885, 990, 995, 996, 1190, 1210, 1212,
Working Diameter:	1290, 1390, 1410, 1412, 1490, 1494,
	1594, 1690, 1694
	


<b>KR-81747955N</b>	OEM:
Max. Working Pressure: 0.8 BAR	
Pressure (PSI): 11.6 PSI	<b>Fitment Information:</b>
Inside Diameter: 36.5mm	885, 990, 995, 996, 1190, 1194, 1210,
Working Diameter: 55mm	1212, 1290, 1294, 1390, 1394, 1490,
	1494, 1594, 1690, 1694
	


<b>KR-972501</b>	OEM:
Max. Working Pressure: 0.8 BAR	
Pressure (PSI): 11.6 PSI	<b>Fitment Information:</b>
Inside Diameter: 39mm	Engine 35501, A4155A, AD3/49A,
Working Diameter: 55mm	AD3/55A
	Tractor 770, 780, 880, 1200
	

<b>KR-AL56759N</b>	OEM:
Max. Working Pressure: 0.6 BAR	
Pressure (PSI):	<b>Fitment Information:</b>
Inside Diameter: 38mm	Engine 165004, 2200002, 2200004,
Working Diameter: 54mm	220101, 220105, 330001, 330002,
	330101, 330102, 355011, 449001,
	455009, 455011, 455031, 455051,
	455071, AD3/55, AD4/55, AD4/55T,
	AD6/55, AD6/55T
	Tractor 885, 990, 995, 996, 1190,
	1194, 1210, 1212, 1290, 1390, 1410, 1412,
	1490, 1494, 1594, 1690, 1694
	


<b>KR-K906196N</b>	OEM: K906196
Max. Working Pressure: 0.3 BAR	
Pressure (PSI): 4 PSI	<b>Fitment Information:</b>
Inside Diameter:	Engine 35501, A4155A, AD3/49A,
Working Diameter:	AD3/55A
	Tractor 770, 780, 880, 885, 990, 995,
	996, 1200, 1210, 1212, 1410, 1412
	

<b>KR-VPE3200</b>	OEM: 80889R91, E81942, K945362
Max. Working Pressure: 0.5 BAR	
Pressure (PSI): 7 PSI	<b>Fitment Information:</b>
Inside Diameter: 38mm	Engine 165004, 2200002, 2200004,
Working Diameter: 54mm	220101, 220105, 330001, 330002,
	330101, 330102, 355011, 449001,
	455009, 455011, 455031, 455051,
	455071, AD3/55, AD4/55, AD4/55T,
	AD6/55, AD6/55T
	Tractor 885, 990, 995, 996, 1190,
	1194, 1210, 1212, 1290, 1390, 1410, 1412,
	1490, 1494, 1594, 1690, 1694
	


<b>KR-VPE3201</b>	OEM: K906196
Max. Working Pressure: 0.3 BAR	
Pressure (PSI): 4 PSI	<b>Fitment Information:</b>
Inside Diameter:	Engine 35501, A4155A, AD3/49A,
Working Diameter:	AD3/55A
	Tractor 770, 780, 880, 1200
	

<b>KR-VPE3215</b>	OEM: K922544, K945363
Max. Working Pressure: 0.3 BAR	
Pressure (PSI): 4 PSI	<b>Fitment Information:</b>
Inside Diameter:	Engine 35501, 355011, 449001,
Working Diameter:	455009, 455011, 455031, 455051,
	455071, A4155A, AD3/55A
	Tractor 780, 880, 885, 990, 995, 996,
	1200, 1210, 1212, 1410, 1412
	


# Deutz-Fahr


<b>KR-83957211N</b>	<b>OEM:</b>
Max. Working Pressure: 0.9 BAR	
Pressure (PSI): 13 PSI	<b>Fitment Information:</b>
Inside Diameter:	110, 130, 150, AGROFARM 85, 100, AGROLUX 75, 95, F70, F80, AGROPLUS 75, AGROTRAC 125, 610, 620, AGROTRON 85, 100MK2, 110MK2, 130 NEW, 150MK2, 195, 200MK2, F60, F70, F80, F90
Working Diameter:	
	


# Fendt


KR-VPE3228	OEM:
Max. Working Pressure: 0.7 BAR	
Pressure (PSI): 10 PSI	<b>Fitment Information:</b>
Inside Diameter:	102LS, 102LSA, 102SA, 103LS, 103LSA, 103SA, 104LS, 104LSA, 104SA,
Working Diameter:	FARMER 102S, 103S, 104S
	




<b>KR-3475308M1N</b>	OEM:
Max. Working Pressure: 0.5 BAR	
Pressure (PSI): 7 PSI	<b>Fitment Information:</b>
Inside Diameter:	45/66, 45/76, 50/66, 50/86, 55/66, 55/75, 55/76, 55/85, 55/86, 55/88, 55/90, 56/66, 60/66, 60/75, 60/76, 60/86, 60/88, 60/90, 60/93, 60/94, 62/86, 65/66, 65/88, 65/90, 65/93, 65/94, 70/66, 70/75, 70/76, 70/86, 70/88, 70/90, 72/86, 72/93, 72/94, 80/66, 80/75, 80/76, 80/88, 80/90, 82/85, 82/86, 82/93, 82/94, 85/90, 88/85, 88/93, 88/94, 90/90, 100/90, 110/90, F100, 110, 115, 120, 130, 140, L60, 65, 75, 85, 95
Working Diameter:	
	


<b>KR-4999682N</b>	OEM: 4999682
Max. Working Pressure: 0.7 BAR	
Pressure (PSI): 10 PSI	<b>Fitment Information:</b>
Inside Diameter:	250, 255, 300, 315, 350, 400, 411, 415, 420, 421, 431, 446, 450, 460, 466, 470, 480, 500, 505, 540, 550, 566, 570, 580, 600, 605, 640, 650, 655, 666, 670, 680, 750, 766, 780, 850, 880, 880/5, 900, 980, 1000, 1180, 1280, 1300, 1355, 1380, 1580, 1880, 35/66, 45/66, 45/76, 50/66, 50/86, 55/46, 55/56, 55/65, 55/66, 55/75, 55/76, 55/85, 55/86, 55/88, 55/90, 56/66, 60/46, 60/66, 60/76, 60/86, 60/88, 60/90, 60/93, 60/94, 62/86, 65/46, 65/56, 65/66, 65/88, 65/90, 65/93, 65/94, 70/56, 70/66, 70/76, 70/86, 70/88, 70/90, 72/86, 72/93, 72/94, 80/66, 80/76, 80/88, 80/90, 82/85, 82/86, 82/93, 82/94, 85/90, 88/85, 88/93, 88/94, 90/90, 95/55, 100/55, 100/90, 110/90, 110/90, 115, 120, 130
Working Diameter:	
	

<b>KR-81747955N</b>	OEM: 81747955
Max. Working Pressure: 0.8 BAR	
Pressure (PSI): 11.6 PSI	<b>Fitment Information:</b>
Inside Diameter: 36.5mm	250, 255, 300, 315, 350, 400, 411, 415, 420, 421, 431, 446, 450, 460, 466, 470, 480, 500, 505, 540, 550, 566, 570, 580, 600, 605, 640, 650, 655, 666, 670, 680, 750, 766, 780, 850, 880, 880/5, 900, 980, 1000, 1180, 1280, 1300, 1355, 1380, 1580, 1880, 35/66, 45/66, 45/76, 50/66, 50/86, 55/46, 55/56, 55/65, 55/66, 55/75, 55/76, 55/85, 55/86, 55/88, 55/90, 56/66, 60/46, 60/56, 60/65, 60/66, 60/75, 60/76, 60/86, 60/88, 60/90, 60/93, 60/94, 62/86, 65/46, 65/56, 65/66, 65/88, 65/90, 65/93, 65/94, 70/56, 70/65, 70/66, 70/75, 70/76, 70/86, 70/88, 70/90, 72/86, 72/93, 72/94, 80/66, 80/75, 80/76, 80/88, 80/90, 82/85, 82/86, 82/93, 82/94, 85/55, 85/90, 88/85, 88/93, 88/94, 90/90, 95/55, 100/55, 100/90, 110/90, 160/55, F110, 115, 120, 130, L60, 65, 75, 85, 95
Working Diameter: 55mm	
	


<b>KR-83957211N</b>	OEM: 83957211
Max. Working Pressure: 0.9 BAR	
Pressure (PSI): 13 PSI	<b>Fitment Information:</b>
Inside Diameter:	115/90, 130/90, 140/90, 160/90, 180/90, F140
Working Diameter:	
	


<b>KR-9966958N</b>	OEM: 9966958
Max. Working Pressure:	
Pressure (PSI):	<b>Fitment Information:</b>
Inside Diameter: 37mm	450, 466, 480, 500, 540, 566, 640, 650, 666, 750, 850, 45/66, 50/66, 55/66, 60/66, 65/66, 70/66, 80/66
Working Diameter: 55mm	
	

<b>KR-AL56759N</b>	OEM:
Max. Working Pressure: 0.6 BAR	
Pressure (PSI):	<b>Fitment Information:</b>
Inside Diameter: 38mm	250, 255, 300, 315, 350, 400, 411, 415, 420, 421, 431, 446, 450, 460, 466, 470, 480, 500, 505, 540, 550, 566, 570, 580, 600, 605, 640, 650, 655, 666, 670, 680, 750, 766, 780, 850, 880, 880/5, 900, 980, 1000, 1180, 1280, 1300, 1355, 1380, 1580, 1880, 35/66, 45/66, 45/76, 50/66, 50/86, 55/46, 55/56, 55/65, 55/66, 55/75, 55/76, 55/85, 55/86, 55/88, 55/90, 56/66, 60/46, 60/56, 60/65, 60/66, 60/75, 60/76, 60/86, 60/88, 60/90, 60/93, 60/94, 62/86, 65/46, 65/56, 65/66, 65/88, 65/90, 65/93, 65/94, 70/56, 70/65, 70/66, 70/75, 70/76, 70/86, 70/88, 70/90, 72/86, 72/93, 72/94, 80/66, 80/75, 80/76, 80/88, 80/90, 82/85, 82/86, 82/93, 82/94, 85/55, 85/90, 88/85, 88/93, 88/94, 90/90, 95/55, 100/55, 100/90, 110/90, 160/55, F100, 110, 115, 120, 130, L60, 65, 75, 85, 95
Working Diameter: 54mm	
	

<b>KR-VPE3228</b>	OEM: 4999682
Max. Working Pressure: 0.7 BAR	
Pressure (PSI): 10 PSI	<b>Fitment Information:</b>
Inside Diameter:	580, 680, 780, 880, 880/5, 980, 1180, 1280, 1300, 1380, 1580, 1880, 45/66, 50/66, 55/46, 55/56, 55/66, 55/88, 55/90, 60/46, 60/56, 60/66, 60/90, 60/93, 60/94, 65/46, 65/56, 65/66, 65/90, 65/93, 65/94, 70/56, 70/66, 70/90, 72/93, 72/94, 80/66, 80/90, 82/93, 82/94, 85/90, 88/94, 90/90, 95/90, 100/90, 110/90, F100, 110, 115, 120, 130
Working Diameter:	
	


# Ford

<b>KR-3475308M1N</b>	OEM:
Max. Working Pressure: 0.5 BAR	
Pressure (PSI): 7 PSI	<b>Fitment Information:</b>
Inside Diameter:	3435, 3935, 4135
Working Diameter:	
	


<b>KR-4999682N</b>	OEM: 4999682
Max. Working Pressure: 0.7 BAR	
Pressure (PSI): 10 PSI	<b>Fitment Information:</b>
Inside Diameter:	3435, 3935, 4135
Working Diameter:	
	

<b>KR-81711544N</b>	OEM: 376809, 81711544
Max. Working Pressure:	
Pressure (PSI):	<b>Fitment Information:</b>
Inside Diameter: 70mm	DEXTA, MAJOR, SUPER DEXTA, SUPER MAJOR
Working Diameter: 55.9mm	
	


<b>KR-81747955N</b>	OEM: 81747955
Max. Working Pressure: 0.8 BAR	
Pressure (PSI): 11.6 PSI	<b>Fitment Information:</b>
Inside Diameter: 36.5mm	231, 233, 234, 333, 334, 335, 420, 515, 531, 532, 535, 550, 555, 2000, 2100, 2110, 2120, 2150, 2300, 2310, 2600, 2610, 2810, 2910, 3000, 3100, 3120, 3150, 3230, 3300, 3310, 3430, 3435, 3500, 3600, 3610, 3830, 3900, 3910, 3930, 3935, 4000, 4030, 4100, 4110, 4130, 4135, 4140, 4190, 4200, 4230, 4340, 4400, 4410, 4430, 4500, 4600, 4610, 4630, 4830, 5000, 5030, 5100, 5110, 5190, 5200, 5340, 5600, 5610, 5700, 5900, 6410, 6600, 6610, 6700, 6710, 6810, 7000, 7100, 7200, 7410, 7600, 7610, 7700, 7710, 8000, 8200, 8600, 8700, 9000, 9200, 9600, 9700, TW10, TW20, TW30
Working Diameter: 55mm	
	


<b>KR-83957211N</b>	OEM: 83957211
Max. Working Pressure: 0.9 BAR	
Pressure (PSI): 13 PSI	<b>Fitment Information:</b>
Inside Diameter:	3230, 3430, 3930, 4130, 4630, 4830, 5030, 5610, 5640, 6610, 6640, 6810, 7010, 7610, 7740, 7810, 7840, 7910, 8010, 8210, 8240, 8340, 8530, 8630, 8670, 8730, 8770, 8830, 8870, 8970, 9700, TW5, TW10, TW15, TW20, TW25, TW30, TW35
Working Diameter:	
	


<b>KR-AL56759N</b>	OEM:
Max. Working Pressure: 0.6 BAR	
Pressure (PSI):	<b>Fitment Information:</b>
Inside Diameter: 38mm	Engine BSD326, 329, 330, 332, 333, 438, 442, 442T, 444, 444T, 666, 666T, 666T1, Tractor 231, 233, 234, 333, 334, 335, 420, 515, 531, 532, 535, 550, 555, 654, 754, 764, 774, 944, 964, 974, 1164, 1164TWM 1184TW, 2000, 2100, 2110, 2120, 2150, 2300, 2310, 2600, 2610, 2810, 2910, 3000, 3055, 3100, 3120, 3150, 3230, 3300, 3310, 3430, 3435, 3500, 3600, 3610, 3830, 3900, 3910, 3930, 3935, 4000, 4030, 4100, 4110, 4130, 4135, 4140, 4190, 4200, 4230, 4340, 4410, 4430, 4500, 4600, 4610, 4630, 4830, 5000, 5030, 5100, 5110, 5190, 5200, 5340, 5600, 5610, 5700, 5900, 6410, 6600, 6610, 6700, 6810, 7000, 7100, 7200, 7410, 7600, 7610, 7700, 7710, 8000, 8200, 8530, 8600, 8630, 8700, 8730, 8830, 9000, 9200, 9600, 9700, TW5, TW10, TW15, TW20, TW25, TW30, TW35
Working Diameter: 54mm	
	


<b>KR-VPE3200</b>	OEM: 2400E8100A, 80076896, 81645535, 81747955, 81855444, 83935904, E2NN8100AA
Max. Working Pressure: 0.5 BAR	
Pressure (PSI): 7 PSI	<b>Fitment Information:</b>
Inside Diameter: 38mm	Engine BSD326, 329, 330, 332, 333, 438, 442, 442T, 444, 444T, 666, 666T, 666T1, Tractor 654, 754, 764, 774, 944, 964, 974, 1164, 1164TW, 1184TW, 2000, 2310, 2600, 2610, 2810, 2910, 3000, 3055, 3230, 3430, 3600, 3610, 3900, 3910, 3930, 4000, 4100, 4110, 4130, 4600, 4610, 4630, 5000, 5110, 5600, 5610, 5700, 5900, 6410, 6600, 6610, 6700, 6710, 6810, 7000, 7410, 7600, 7610, 7700, 7710, 8000, 8200, 8530, 8600, 8630, 8700, 8730, 8830, 9000, 9200, 9600, 9700, TW5, TW10, TW15, TW20, TW25, TW30, TW35
Working Diameter: 54mm	
	

<b>KR-VPE3220</b>	OEM: 211E8100A1, 83935905, 83957211, E2NN8100BA
Max. Working Pressure: 0.9 BAR	
Pressure (PSI): 13 PSI	<b>Fitment Information:</b>
Inside Diameter:	Engine BSD326, 329, 330, 332, 333, 438, 442, 442T, 444, 444T, 666, 666T, 666T1, Tractor 654, 754, 764, 774, 944, 964, 974, 1164, 1164TW, 1184TW, 2000, 2310, 2600, 2610, 2810, 2910, 3000, 3055, 3230, 3430, 3600, 3610, 3900, 3910, 3930, 4000, 4100, 4110, 4130, 4600, 4610, 4630, 4830, 5000, 5030, 5110, 5600, 5610, 5640, 5700, 5900, 6410, 6600, 6610, 6640, 6700, 6710, 6810, 7000, 7410, 7600, 7610, 7700, 7710, 7740, 7840, 7910, 8000, 8200, 8210, 8240, 8340, 8530, 8600, 8630, 8700, 8730, 8830, 9000, 9200, 9600, 9700, TW5, TW10, TW15, TW20, TW25, TW30, TW35
Working Diameter:	
	


<b>KR-VPE3221</b>	OEM: 83955240, E5NN8100AA
Max. Working Pressure: 0.7 BAR	
Pressure (PSI): 10 PSI	<b>Fitment Information:</b>
Inside Diameter:	Engine BSD326, 329, 330, 332, 333, 438, 442, 442T, 444, 444T, 666, 666T, 666TI
Working Diameter:	Tractor 2000, 2310, 2600, 2610, 2810, 2910, 3000, 3055, 3230, 3430, 3600, 3610, 3900, 3910, 3930, 4000, 4100, 4110, 4130, 4600, 4610, 4630, 5000, 5110, 5600, 5610, 5700, 5900, 6410, 6600, 6610, 6700, 6710, 6810, 7000, 7410, 7600, 7610, 7700, 7710, 8000, 8200, 8530, 8600, 8630, 8700, 8730, 8830, 9000, 9200, 9600, 9700, TW5, TW10, TW15, TW20, TW25, TW30, TW35
	

<b>KR-VPE3228</b>	OEM: 4999682
Max. Working Pressure: 0.7 BAR	
Pressure (PSI): 10 PSI	<b>Fitment Information:</b>
Inside Diameter:	3435, 3935
Working Diameter:	
	


<b>KR-VPE3243</b>	OEM: 81874132, 83972021, E8NN8C083BB
Max. Working Pressure:	
Pressure (PSI):	<b>Fitment Information:</b>
Inside Diameter:	Engine BSD329, 332, 333, 442, 444, 444T, 666, GENESIS 4.4, 5.0T, 6.6, POWERSTAR 4.4, 5.0, 5.0T, 6.6, 7.5, 7.5T
Working Diameter:	Tractor 2610, 2910, 3610, 3910, 4610, 5610, 5640, 6410, 6610, 6640, 6710, 6810, 7410, 7610, 7710, 7740, 7810, 7840, 7910, 8210, 8240, 8340
	

<b>KR-VPE3251</b>	OEM: 0150142, E1ADKN9030B
Max. Working Pressure: 0.3 BAR	
Pressure (PSI): 4 PSI	<b>Fitment Information:</b>
Inside Diameter:	DEXTA, SUPER DEXTA
Working Diameter:	
	


# FPT

KR-VPE3228	OEM:
Max. Working Pressure: 0.7 BAR	
Pressure (PSI): 10 PSI	<b>Fitment Information:</b>
Inside Diameter:	Engine F5C, NEF4.5, NEF4.5T
Working Diameter:	
	


# Hurlimann


<b>KR-83957211N</b>	<b>OEM:</b>
Max. Working Pressure: 0.9 BAR	
Pressure (PSI): 13 PSI	<b>Fitment Information:</b>
Inside Diameter:	H358, 468, 468.4, 476, 478, 478.4, 481, 488, 491, H6115, 6135, 6165, 6190, SX1200, 1350, 1500, 1600, 1800, 2000, XA606, 607, XN706, 707, 708, 709, XT85, 95, 105, 110, 115, 130, 140, 160, 908, 909, 910.4, 910.6, 911, 913
Working Diameter:	
	

<b>KR-VPE3220</b>	OEM: 211E8100A1, 83935905, 83957211, E2NN8100BA
Max. Working Pressure: 0.9 BA	
Pressure (PSI): 13 PSI	<b>Fitment Information:</b>
Inside Diameter:	Engine 8035.05, 8035.06, 8035.25, 8045.05, 8045.06, 8045.25
Working Diameter:	
	

<b>KR-VPE3228</b>	OEM: 4999682
Max. Working Pressure: 0.7 BAR	
Pressure (PSI): 10 PSI	<b>Fitment Information:</b>
Inside Diameter:	Engine 8035.05, 8035.06, 8035.25, 8035.45, 8045.05, 8045.06, 8045.25, 8045.45
Working Diameter:	
	

# John Deere


<b>KR-81747955N</b>	OEM:
Max. Working Pressure: 0.8 BAR	
Pressure (PSI): 11.6 PSI	<b>Fitment Information:</b>
Inside Diameter: 36.5mm	2250, 2450, 2650, 2850, 2855, 3050, 3150, 3350, 3650
Working Diameter: 55mm	
	

<b>KR-972501</b>	OEM:
Max. Working Pressure: 0.8 BAR	
Pressure (PSI): 11.6 PSI	<b>Fitment Information:</b>
Inside Diameter: 39mm	2000, 2100, 2200, 2300, 2400, 2700, 2800
Working Diameter: 55mm	
	

<b>KR-AL38374N</b>	OEM: AL38374
Max. Working Pressure: 0.5 BAR	
Pressure (PSI): 7 PSI	<b>Fitment Information:</b>
Inside Diameter: 38mm	840, 940, 1040, 1140, 1350, 1550, 1630, 1640, 1750, 1840, 1850, 1950, 2040, 2140, 2150, 2240, 2350, 2550, 2750, 2940, 2950, 3040, 3140, 3150, 3340, 3640
Working Diameter: 55mm	
	


<b>KR-AL56759N</b>	OEM: AL56759
Max. Working Pressure: 0.6 BAR	
Pressure (PSI):	<b>Fitment Information:</b>
Inside Diameter: 38mm	Engine 3179D, 4239D, 4239T, 6359D, 6359T
Working Diameter: 54mm	Tractor 840, 940, 1040, 1140, 1350, 1550, 1640, 1750, 1840, 1850, 2040, 2140, 2150, 2155, 2250, 2255, 2355, 2450, 2555, 2650, 2755, 2850, 2855, 2955, 3040, 3050, 3140, 3150, 3155, 3340, 3350, 3640, 3650
	

<b>KR-AL76661N</b>	OEM: AL76661
Max. Working Pressure: 0.9 BAR	
Pressure (PSI): 13 PSI	<b>Fitment Information:</b>
Inside Diameter:	Engine 4039T, 4045D, 4045H, 4045T, 5030T, 6059T, 6068D, 6068H, 6068T, 6081H, 6105H, 6125H, Tractor 5080, 5090, 5100, 5225, 5325, 5415, 5425, 5525, 5603, 5615, 5620, 5625, 5715, 5720, 5725, 5820, 6010, 6020, 6100, 6110, 6120, 6200, 6205, 6210, 6215, 6220, 6300, 6310, 6320, 6400, 6405, 6410, 6415, 6420, 6425, 6500, 6505, 6506, 6510, 6515, 6520, 6600, 6605, 6610, 6615, 6620, 6715, 6800, 6810, 6820, 6900, 6910, 6920, 7200, 7210, 7400, 7405, 7410, 7420, 7425, 7500, 7510, 7520, 7525, 9100, 9120, 9200, 9220, 9300, 9320, 9400, 9420, 9520, 9620, SE6010, SE6020, SE6100, SE6110, SE6120, SE6200, SE6210, SE6220, SE6300, SE6310, SE6320, SE6400, SE6410, SE6420, SE6510, SE6520, SE6610, SE6620, SE6920
Working Diameter:	
	

<b>KR-AL78005N</b>	OEM: AL78005
Max. Working Pressure:	
Pressure (PSI):	<b>Fitment Information:</b>
Inside Diameter:	5080, 5090, 5100, 5620, 5720, 5820, 6010, 6020, 6100, 6110, 6120, 6130, 6200, 6205, 6210, 6215, 6220, 6225, 6230, 6300, 6310, 6320, 6325, 6330, 6400, 6405, 6410, 6415, 6420, 6425, 6430, 6500, 6505, 6506, 6510, 6515, 6520, 6525, 6530, 6534, 6600, 6605, 6610, 6615, 6620, 6630, 6715, 6800, 6810, 6820, 6830, 6900, 6910, 6920, 6930, 7130, 7200, 7210, 7220, 7230, 7320, 7330, 7400, 7405, 7410, 7420, 7425, 7430, 7500, 7510, 7520, 7525, 7530, SE6010, SE6020, SE6100, SE6110, SE6120, SE6200, SE6210, SE6220, SE6300, SE6310, SE6320, SE6400, SE6410, SE6420, SE6510, SE6520, SE6610, SE6620, SE6920
Working Diameter:	
	


<b>KR-AT29054N</b>	OEM: AT29054
Max. Working Pressure: 0.4 BAR	
Pressure (PSI):	<b>Fitment Information:</b>
Inside Diameter: 37mm	820, 830, 840, 920, 930, 940, 1020, 1030, 1040, 1120, 1130, 1140, 1530, 1630, 1640, 1830, 1840, 2020, 2030, 2040, 2120, 2130, 2140, 2240, 2350, 2440, 2550, 2750, 2840, 2940, 2950, 3030, 3040, 3120, 3130, 3140, 3340
Working Diameter: 57mm	
	


<b>KR-K906196N</b>	OEM:
Max. Working Pressure: 0.3 BAR	
Pressure (PSI): 4 PSI	<b>Fitment Information:</b>
Inside Diameter:	2000, 2100, 2200, 2300, 2400, 2700, 2800
Working Diameter:	
	

<b>KR-VPE3200</b>	OEM: AL56759
Max. Working Pressure: 0.5 BAR	
Pressure (PSI): 7 PSI	<b>Fitment Information:</b>
Inside Diameter: 38mm	Engine 4239D, 4239T, 6359D, 6359T, Tractor 2250, 2355, 2450, 2555, 2650, 2755, 2850, 2855, 3050, 3150, 3350, 3650
Working Diameter: 54mm	
	


<b>KR-VPE3201</b>	OEM:
Max. Working Pressure: 0.3 BAR	
Pressure (PSI): 4 PSI	<b>Fitment Information:</b>
Inside Diameter:	2000, 2100, 2200, 2300, 2400, 2700, 2800
Working Diameter:	
	


<b>KR-VPE3202</b>	OEM: AT29054
Max. Working Pressure: 0.5 BAR	
Pressure (PSI): 7 PSI	<b>Fitment Information:</b>
Inside Diameter: 37mm	Engine 3164D, 3179D, 4202D, 4219D, 4239D, 6303D, 6329D, 6359D, Tractor 820, 830, 840, 920, 930, 940, 1020, 1030, 1040, 1120, 1130, 1140, 1630, 1640, 1830, 1840, 2020, 2030, 2040, 2120, 2130, 2140, 2150, 2155, 2255, 2940, 3030, 3040, 3120, 3130, 3140, 3340
Working Diameter: 57mm	
	

<b>KR-VPE3210</b>	OEM: AL38374
Max. Working Pressure: 0.5 BAR	
Pressure (PSI): 7 PSI	<b>Fitment Information:</b>
Inside Diameter: 38mm	Engine 3179D, 4239D, 4239T, 6359D, Tractor 840, 940, 1040, 1140, 1350, 1550, 1640, 1750, 1840, 1850, 1950, 2040, 2140, 2150, 2155, 2255, 3040, 3140, 3150, 3340, 3640
Working Diameter: 55mm	
	

<b>KR-VPE3252</b>	OEM: RE71863
Max. Working Pressure: 0.9 BAR	
Pressure (PSI): 14 PSI	<b>Fitment Information:</b>
Inside Diameter:	Engine 3029D, 3029T, 4045D, 4045T
Working Diameter:	Tractor 5103, 5105, 5203, 5205, 5210, 5215, 5220, 5303, 5310, 5315, 5320, 5403, 5410, 5415, 5420, 5510, 5515, 5520, 5605, 5615, 5705
	


<b>KR-VPE3253</b>	OEM: AL76661
Max. Working Pressure: 0.9 BAR	
Pressure (PSI): 13 PSI	<b>Fitment Information:</b>
Inside Diameter:	Engine 4039T, 4045D, 4045H, 4045T, 5030T, 6059T, 6068D, 6068H, 6068T, 6081H, 6105H, 6125H
Working Diameter:	Tractor 5080, 5090, 5100, 5225, 5325, 5415, 5425, 5525, 5603, 5615, 5620, 5625, 5715, 5720, 5725, 5820, 6010, 6020, 6100, 6110, 6120, 6200, 6210, 6220, 6300, 6310, 6320, 6400, 6410, 6420, 6500, 6510, 6520, 6600, 6610, 6620, 6800, 6810, 6820, 6900, 6910, 6920, 7210, 7410, 7425, 7510, 9100, 9120, 9220, 9300, 9320, 9400, 9420, 9520, 9620, SE6010, SE6020, SE6100, SE6110, SE6120, SE6200, SE6210, SE6220, SE6300, SE6310, SE6320, SE6400, SE6410, SE6420, SE6510, SE6520, SE6620, SE6920
	

<b>KR-VPE3259</b>	OEM:
Max. Working Pressure: 1.1 BAR	
Pressure (PSI): 16 PSI	<b>Fitment Information:</b>
Inside Diameter:	Engine 6068H
Working Diameter:	
	


<b>KR-VPE3262</b>	OEM:
Max. Working Pressure: 0.8 BAR	
Pressure (PSI): 11.6 PSI	<b>Fitment Information:</b>
Inside Diameter:	Engine 6068H, 6068T
Working Diameter:	
	





# Lamborghini

<b>KR-83957211N</b>	<b>OEM:</b>
Max. Working Pressure: 0.9 BAR	
Pressure (PSI): 13 PSI	<b>Fitment Information:</b>
Inside Diameter:	674-70, 775F, 880F, 990F, 1106, 1306, 1506, AGILE 660, 770, 880, 990, C674-70, C774-80, C874-90, CF.78, CF.88, CF.98, CHAMPION 120, 135, 150, 160, 180, 200, FORMULA 115, 135, GRAND PRIX 674-70, 774-80, 874-90, GRIMPER 570, HIGH CLEARANCE 90, PREMIUM 950, 1050, 1060, 1100, 1300, 1600, 1800, R4.85, 4.95, 4.105, 4.110, R5.115, 5.130, R7.175, 7.190, 7.200, RACING 150, 165, 190, SPRINT 664-60, 674-70, TRIUMPH 90, 100
Working Diameter:	
	


# Landini

<b>KR-3134146R1N</b>	OEM: 180224M92
Max. Working Pressure: 0.8 BAR	
Pressure (PSI): 11.6 PSI	<b>Fitment Information:</b>
Inside Diameter: 38mm	9550, 16000
Working Diameter: 55mm	
	

<b>KR-3475308M1N</b>	OEM: 3475308M1, 968976M1
Max. Working Pressure: 0.5 BAR	
Pressure (PSI): 7 PSI	<b>Fitment Information:</b>
Inside Diameter:	16500
Working Diameter:	
	

<b>KR-83957211N</b>	OEM:
Max. Working Pressure: 0.9 BAR	
Pressure (PSI): 13 PSI	<b>Fitment Information:</b>
Inside Diameter:	STARLAND 210, 240, 270
Working Diameter:	
	

<b>KR-AL56759N</b>	OEM:
Max. Working Pressure: 0.6 BAR	
Pressure (PSI):	<b>Fitment Information:</b>
Inside Diameter: 38mm	16500
Working Diameter: 54mm	
	

<b>KR-VPE3200</b>	OEM: 968816M2
Max. Working Pressure: 0.5 BAR	
Pressure (PSI): 7 PSI	<b>Fitment Information:</b>
Inside Diameter: 38mm	16500
Working Diameter: 54mm	
	


<b>KR-VPE3220</b>	OEM:
Max. Working Pressure: 0.9 BAR	
Pressure (PSI): 13 PSI	<b>Fitment Information:</b>
Inside Diameter:	STARLAND 210, 240, 270
Working Diameter:	
	


<b>KR-VPE3256</b>	OEM: 3671126M91
Max. Working Pressure: 1 BAR	
Pressure (PSI): 14 PSI	<b>Fitment Information:</b>
Inside Diameter:	5.090D, 5.100D, 5.110D, 5-090, 5-100, 5-110, 5-115, 7-145, 7-165, 7-180, 7-185, 7-190, 7-195, 7-205, 7-210, 7-220, 7-230, 7-235, LANDPOWER 125, 135, 145, 165, POWERMASTER 180, 190, 200, 210, 220, 230, REX 60, 70, 75, 80, 85, 90, 95, 100, 105, 110, 120, REX4-70, 4-80, 4-90, 4-100
Working Diameter:	
	

<b>KR-VPE3263</b>	OEM: 3541361M91, 4203305M1
Max. Working Pressure: 0.7 BAR	
Pressure (PSI): 10 PSI	<b>Fitment Information:</b>
Inside Diameter:	85, 95, 105, 125, 135, 145, 165, 185, GHIBLI 80, 85, 90, 95, 100, 105, LANDPOWER 115, 125, 130, 145, 160, 165, 185, LEGEND 105, 115, 130, 145, 165, MYTHOS 90, 100, 105, 110, 115, NEW LEGEND 115, 120, 130, 140, 160, 180, VISION 80, 90, 100
Working Diameter:	
	


# Leyland


<b>KR-AL56759N</b>	OEM:
Max. Working Pressure: 0.6 BAR	
Pressure (PSI):	<b>Fitment Information:</b>
Inside Diameter: 38mm	Engine 2.8T, 2.8TD, 3.4TD, 3.8T, 3.8TD, 4.98DT, 4.98TT, 6.98NT,
Working Diameter: 54mm	Tractor 245, 253, 255, 262, 270, 272, 282, 285, 344, 384, 462, 472, 482, 485, 502, 602, 604, 702, 704, 802, 804, 2100, 4100, 3/45, 4/65
	


<b>KR-VPE3200</b>	OEM: CRC112, MBU1229
Max. Working Pressure: 0.5 BAR	
Pressure (PSI): 7 PSI	<b>Fitment Information:</b>
Inside Diameter: 38mm	Engine 2.8T, 2.8TD, 3.4TD, 3.8T, 3.8TD, 4.98DT, 4.98TT, 6.98NT,
Working Diameter: 54mm	Tractor 245, 253, 255, 262, 270, 272, 282, 285, 344, 384, 462, 472, 482, 485, 502, 602, 604, 702, 704, 802, 804, 2100, 4100, 3/45, 4/65
	


<b>KR-VPE3215</b>	OEM:
Max. Working Pressure: 0.3 BAR	
Pressure (PSI): 4 PSI	<b>Fitment Information:</b>
Inside Diameter:	Engine 2.8T, 2.8TD, 3.4TD, 3.8T, 3.8TD, 4.98DT, 4.98TT, 6.98NT,
Working Diameter:	Tractor 245, 253, 255, 262, 270, 272, 282, 285, 344, 384, 462, 472, 482, 485, 502, 602, 604, 702, 704, 802, 804, 2100, 4100, 3/45, 4/65
	


# Massey Ferguson

<b>KR-1874445M94GP</b>	OEM: 1874445M93, 1874445M94
Max. Working Pressure:	
Pressure (PSI):	<b>Fitment Information:</b>
Inside Diameter:	230, 245, 253, 265, 275, 285, 290, 298, 550, 560, 565, 575, 590
Working Diameter:	
	


<b>KR-24850020N</b>	OEM: 24820020
Max. Working Pressure:	
Pressure (PSI):	<b>Fitment Information:</b>
Inside Diameter: 36.5mm	135, 148, 165, 168, 178, 185, 188
Working Diameter: 55mm	
	


<b>KR-3134146R1N</b>	OEM: 180224M92
Max. Working Pressure: 0.8 BAR	
Pressure (PSI): 11.6 PSI	<b>Fitment Information:</b>
Inside Diameter: 38mm	230, 340, 342, 350, 352, 355, 360, 362, 365, 372, 374, 375, 382, 384, 390, 390T, 393, 394, 398, 399, 440, 465, 475, 490, 565, 575, 590, 592, 675, 690, 698, 698T, 699, 2620, 2625, 2640, 2680, 2720, 3050, 3060, 3065, 3070, 3075, 3085, 3095, 3115, 3120, 3125, 3635, 3645, 3655, 3670, 3680, 3690, 4215, 4220, 4225, 4235, 4240, 4245, 4255, 4260, 4265, 4270, 4315, 4320, 4325, 4335, 4345, 4355, 4360, 4365, 4370, 5300, 5310, 5320, 5340, 5355, 5360, 5365, 6110, 6120, 6130, 6140, 6150, 6160, 6170, 6180, 6190, 6235, 6245, 6255, 6260, 6265, 6270, 6280, 6290, 8110, 8120, 8130, 8140, 8150, 8160, 8170, 8180, 8210, 8220, 8240, 8250, 8260
Working Diameter: 55mm	
	


<b>KR-3475308M1N</b>	OEM: 3475308M1
Max. Working Pressure: 0.5 BAR	
Pressure (PSI): 7 PSI	<b>Fitment Information:</b>
Inside Diameter:	35, 65, 133, 135, 140, 145, 148, 152, 155, 158, 165, 175, 765, 865, FE35
Working Diameter:	
	


<b>KR-81747955N</b>	OEM: 968816M2
Max. Working Pressure: 0.8 BAR	
Pressure (PSI): 11.6 PSI	<b>Fitment Information:</b>
Inside Diameter: 36.5mm	352, 2620, 2645, 2685, 2725, 3050, 3060, 3065, 3070, 3080, 3085, 3090, 3095, 3115, 3120, 3125, 3610, 3615, 3630, 3635, 3645, 3650, 3655
Working Diameter: 55mm	
	


<b>KR-AL56759N</b>	OEM:
Max. Working Pressure: 0.6 BAR	
Pressure (PSI):	<b>Fitment Information:</b>
Inside Diameter: 38mm	2645, 2685, 2725, 3050, 3060, 3065, 3070, 3080, 3085, 3090, 3095, 3115, 3120, 3125, 3140, 3610, 3630, 3635, 3645, 3650, 3655, 3660
Working Diameter: 54mm	
	


<b>KR-V33690710</b>	OEM: 33690710, V33690710
Max. Working Pressure:	
Pressure (PSI):	<b>Fitment Information:</b>
Inside Diameter:	4435, 4445, 4455, 5410, 5420, 5425, 5430, 5435, 5440, 5445, 5450, 5455, 5475, 5480, 6445, 6455, 6465, 6470, 6475, 6480, 6485, 6490, 6495, 6497, 6499, 7465, 7475, 7480, 7485, 7490, 7495, 7497, 7499, 5S.105, 5S.115, 5S.125, 5S.135, 5S.145, 8S.225, 8S.245, 8S.265
Working Diameter:	
	

<b>KR-VPE3200</b>	OEM: 968816M2
Max. Working Pressure: 0.5 BAR	
Pressure (PSI): 7 PSI	<b>Fitment Information:</b>
Inside Diameter: 38mm	2645, 2685, 2725, 3050, 3060, 3065, 3070, 3080, 3085, 3090, 3095, 3115, 3120, 3125, 3140, 3610, 3630, 3635, 3645, 3650, 3655, 3660
Working Diameter: 54mm	
	


<b>KR-VPE3202</b>	OEM: 3475308M1, 826772M1
Max. Working Pressure: 0.5 BAR	
Pressure (PSI): 7 PSI	<b>Fitment Information:</b>
Inside Diameter: 37mm	35, 35X, 65, 135, 140, 145, 165, 175, 765, 835, FE35
Working Diameter: 57mm	
	

<b>KR-VPE3204</b>	OEM: 24850017, 24850020, 3637301M1, 885341M1, 885344M1
Max. Working Pressure: 0.7 BAR	
Pressure (PSI): 10 PSI	<b>Fitment Information:</b>
Inside Diameter:	135, 140, 145, 148, 152, 165, 168, 178, 185, 188
Working Diameter:	
	


<b>KR-VPE3206</b>	OEM: 1874445M91, 1874445M92, 1874445M93, 1874445M94
Max. Working Pressure: 0.7 BAR	
Pressure (PSI): 10 PSI	<b>Fitment Information:</b>
Inside Diameter:	230, 240, 250, 255, 265, 275, 285, 290, 298, 550, 560, 565, 575, 590
Working Diameter:	
	


<b>KR-VPE3251</b>	OEM: 0150142, 3637675M1, 3638322M1, 4153, 643595M1, 825702M2
Max. Working Pressure: 0.3 BAR	
Pressure (PSI): 4 PSI	<b>Fitment Information:</b>
Inside Diameter:	TE20, TEA20, TED20, TEF20
Working Diameter:	
	


<b>KR-VPE3257</b>	OEM: 4356380M1
Max. Working Pressure: 1.0 BAR	
Pressure (PSI): 14.5 PSI	<b>Fitment Information:</b>
Inside Diameter:	5608, 5609, 5610, 5611, 5612, 5613, 661,2 6613, 6614, 6615, 6616, 7614, 7615, 7616, 7618, 7619, 7620, 7622, 7624, 7626, 8650, 8660, 8670, 8680, 8690, 8727, 8730, 8732, 8735, 8737
Working Diameter:	
	

<b>KR-VPE3264</b>	OEM: 4296015M1
Max. Working Pressure: 0.95 BAR	
Pressure (PSI): 13.7 PSI	<b>Fitment Information:</b>
Inside Diameter:	5420, 5425, 5430, 5435, 5440, 5445, 5450, 5455, 5460, 5465, 5470, 5475, 5480, 6445, 6455, 6460, 6465, 6470, 6475, 6480, 6485, 6490, 6495, 6497, 6499, 7465, 7475, 7480, 7490, 7495, 7497, 7499, 8650, 8660, 8670, 8680, 8690
Working Diameter:	
	


# McCormick


<b>KR-83957211N</b>	OEM:
Max. Working Pressure: 0.9 BAR	
Pressure (PSI): 13 PSI	<b>Fitment Information:</b>
Inside Diameter:	CX50, 60, 70, 75, 80, 85, 90, 95, 100, 105, MC80, 90, 95, 100, 105, 115, MTX110, 125, 140, 155, 175, 200
Working Diameter:	
	


<b>KR-VPE3255</b>	OEM: 1547924C1, 440729A1, A184079
Max. Working Pressure: 0.0 BAR	
Pressure (PSI): 0 PSI	<b>Fitment Information:</b>
Inside Diameter:	C50, 60, CX50, 60, MTX110, 125, 140, 155, 175, 200
Working Diameter:	
	


<b>KR-VPE3256</b>	OEM: 3671126M91
Max. Working Pressure: 1 BAR	
Pressure (PSI): 14 PSI	<b>Fitment Information:</b>
Inside Diameter:	G-MAX 125, 135, 145, 165, 180, MC120, 135, MTX 120, 135, 145, 150, TTX190, 210, 230, XTX145, 165, 185, X70.50, X70.60, X70.70, X70.80
Working Diameter:	
	

# New Holland

<b>KR-3475308M1N</b>	OEM:
Max. Working Pressure: 0.5 BAR	
Pressure (PSI): 7 PSI	<b>Fitment Information:</b>
Inside Diameter:	3830, 4030, 4230, 4430, 4635, 4835, 5635, 6635, 7635, T4030F, 4040F,
Working Diameter:	TD60, 70, 80, 90, 95, TD55D, 65D, 65F, 75D, 75F, 85D, 85F, TK65, 70, 75, 76, 80, 85, 90, 95, 100, TL70, 80, 90, 100, TL70A, 80A, 90A, 100A, TN55, 60, 65, 70, 75, 80, 85, 95, TT50, 55, 65, 75
	


<b>KR-4274034</b>	OEM: 4274034
Max. Working Pressure:	
Pressure (PSI):	<b>Fitment Information:</b>
Inside Diameter:	4635, L60, 65, 75, 85, 95, T3.50F, 3.55F, 3.65F, 3.75F, T4.55, 4.65, 4.75, 4.85, T4020, 4030, 4040, 4050, 4060, T5030, 5040, 5050, 5060, 5070, TD5.65, 5.75, 5.85, 5.95, 5.105, 5.115, TD5010, 5020, 5030, 5040, 5050, TD60D, 70D, 80D, 85D, 90D, 95D, TL70, 80, 90, 100, TL70A, 80A, 90A, 100A, TN55, 60, 65, 70, 75, 85, 95
Working Diameter:	
	

<b>KR-4999682N</b>	OEM: 4999682
Max. Working Pressure: 0.7 BAR	
Pressure (PSI): 10 PSI	<b>Fitment Information:</b>
Inside Diameter:	G170, 190, 210, 240, L60, 65, 75, 85, 95, M100, 115, 135, 160, TD3.50,
Working Diameter:	TD65F, 75F, 85F
	


<b>KR-81747955N</b>	OEM: 81747955
Max. Working Pressure: 0.8 BAR	
Pressure (PSI): 11.6 PSI	<b>Fitment Information:</b>
Inside Diameter: 36.5mm	230A, 530A, 555A, 3400, 3610, 3910, 3930, 4110, 4610, 4635, 4835, 5635, 6635, 7635, G170, 190, 210, 240, M100, 115, 135, 160, TD60, 70, 80, 90, TD55D, 60D, 65D, 70D, 75D, 80D, 85D, 90D, 95D, TD4020F, 4030F, 4040F, TK65, 76, 85, TL70, 80, 90, 100 TL70A, 80A, 90A, 100A, TN55, 60, 65, 70, 75, 80, 85, 95, TT50, 55, 65, 75
Working Diameter: 55mm	
	


<b>KR-83957211N</b>	OEM: 83957211
Max. Working Pressure: 0.9 BAR	
Pressure (PSI): 13 PSI	<b>Fitment Information:</b>
Inside Diameter:	Combine Harvester TR88, 89, 98, 99 Tractor 3930, 5640, 6640, 7740, 7840, 8240, 8340, 8670, 8770, 8870, 8970, G170, 190, 210, 240, T8010, 8020, 8030, 8040, 8050, T9.390, 9.435, 9.450, 9.480, 9.505, 9.530, 9.560, 9.565, 9.600, 9.615, 9.645, 9.670, 9.700, T9010, 9020, 9030, 9040, 9050, 9060, TD5010, 5020, 5030, 5040, 5050, TD60D, 70D, 80D, 90D, 95D, TG210, 230, 255, 285, TS80, 90, 100, 110, 115
Working Diameter:	
	


<b>KR-AL56759N</b>	OEM:
Max. Working Pressure: 0.6 BAR	
Pressure (PSI):	<b>Fitment Information:</b>
Inside Diameter: 38mm	230A, 530A, 555A, 3400, 3610, 3910, 3930, 4020, 4110, 4230, 4430, 4610, 4635, 4835, 5635, 6635, 7635, G170, 190, 210, 240, M100, 115, 135, 160, TD4020F, 4030F, 4040F, TD60, 70, 80, 90, TD55D, 60D, 65D, 70D, 75D, 80D, 85D, 90D, 95D, TK65, 76, 85, TL70, 80, 90, 100 TL70A, 80A, 90A, 100A, TN55, 60, 65, 70, 75, 80, 85, 95, TT50, 55, 65, 75
Working Diameter: 54mm	
	

<b>KR-VPE3200</b>	OEM: 2400E8100A, 80076896, 81645535, 81747955, 81855444, 83935904, E2NN8100AA
Max. Working Pressure: 0.5 BAR	
Pressure (PSI): 7 PSI	<b>Fitment Information:</b>
Inside Diameter: 38mm	3930
Working Diameter: 54mm	
	

<b>KR-VPE3220</b>	OEM: 211E8100A1, 83935905, 83957211, E2NN8100BA
Max. Working Pressure: 0.9 BAR	
Pressure (PSI): 13 PSI	<b>Fitment Information:</b>
Inside Diameter:	3930, 5640, 6640, 7740, 7840, 8240, 8340, 8670, 8770, 8870, 8970, G170, 190, 210, 240, TD5010, 5020, 5030, 5040, 5050, TD55D, 60D, 65D, 70D, 75D, 80D, 85D, 90D, 95D, TS80, 90, 100, 110, 115
Working Diameter:	
	


<b>KR-VPE3221</b>	OEM: Info
Max. Working Pressure: 0.7 BAR	
Pressure (PSI): 10 PSI	<b>Fitment Information:</b>
Inside Diameter:	3930
Working Diameter:	
	

<b>KR-VPE3228</b>	OEM: Info
Max. Working Pressure: 0.7 BAR	
Pressure (PSI): 10 PSI	<b>Fitment Information:</b>
Inside Diameter:	4635, 4835, 5635, 6635, 7635, L60, 65, 75, 85, 95, TD4020F, 4030F, 4040F, TL70, 80, 90, 100, TL70A, 80A, 90A, 100A
Working Diameter:	
	


<b>KR-VPE3243</b>	OEM: Info
Max. Working Pressure:	
Pressure (PSI):	<b>Fitment Information:</b>
Inside Diameter:	5640, 6640, 7740, 7840, 8240, 8340, TS80, 90, 100, 110, 115
Working Diameter:	
	




# Perkins


<b>KR-3134146R1N</b>	OEM:
Max. Working Pressure: 0.8 BAR	
Pressure (PSI): 11.6 PSI	<b>Fitment Information:</b>
Inside Diameter: 38mm	Engine 4.41, 903-27, 903.27T, 1004-4, 1004-4T, 1004-40, 1004-40T, 1004-40TI, 1004-40TWG, 1004-42, 1006-6, 1006-6T, 1006-60NA, 1006-60T, 1006-60TW, A4.236, A4.248, A4.318.2, A6.354.4, AD3.152, AT3.152.4, AT4.236, AT6.354.4, P4000, P4001T
Working Diameter: 55mm	
	


<b>KR-AL56759N</b>	OEM:
Max. Working Pressure: 0.6 BAR	
Pressure (PSI):	<b>Fitment Information:</b>
Inside Diameter: 38mm	Engine 1006-6, 1006-6T, A4.236, A4.248, A6.354.4, AT4.236, AT6.354.4
Working Diameter: 54mm	
	


<b>KR-VPE3200</b>	OEM:
Max. Working Pressure: 0.5 BAR	
Pressure (PSI): 7 PSI	<b>Fitment Information:</b>
Inside Diameter: 38mm	Engine 1006-6, 1006-6T, A4.236, A4.248, A6.354.4, AT4.236, AT6.354.4
Working Diameter: 54mm	
	

<b>KR-VPE3202</b>	OEM:
Max. Working Pressure: 0.5 BAR	
Pressure (PSI): 7 PSI	<b>Fitment Information:</b>
Inside Diameter: 37mm	Engine A3.144, A3.152, A4.192, A4.236, AD3.152, AD4.203
Working Diameter: 57mm	
	


<b>KR-VPE3204</b>	OEM: 24850017, 24850020
Max. Working Pressure: 0.7 BAR	
Pressure (PSI): 10 PSI	<b>Fitment Information:</b>
Inside Diameter:	Engine A4.236, A4.248, AD3.152
Working Diameter:	
	


<b>KR-VPE3206</b>	OEM:
Max. Working Pressure: 0.7 BAR	
Pressure (PSI): 10 PSI	<b>Fitment Information:</b>
Inside Diameter:	Engine A4.236, A4.248, A4.318.2, AD3.152, AD4.203
Working Diameter:	
	

<b>KR-VPE3251</b>	OEM: 0150142
Max. Working Pressure: 0.3 BAR	
Pressure (PSI): 4 PSI	<b>Fitment Information:</b>
Inside Diameter:	Engine F3.144, F3.152
Working Diameter:	
	


<b>KR-VPE3264</b>	OEM:
Max. Working Pressure: 0.95 BAR	
Pressure (PSI): 13.7 PSI	<b>Fitment Information:</b>
Inside Diameter:	Engine 1104C-44TA, 1104C-E44TA, 1104D-44TA, 1104D-E44TA, 1106C-E60TA, 1106C-E66TA, 1104D-E66TA
Working Diameter:	
	

# SAME


KR-83957211N	OEM:
Max. Working Pressure: 0.9 BAR	
Pressure (PSI): 13 PSI	<b>Fitment Information:</b>
Inside Diameter:	ANTARES II 110, 130, LASER3 140, 160
Working Diameter:	
	


<b>KR-3134146R1N</b>	<b>OEM:</b>
Max. Working Pressure: 0.8 BAR	
Pressure (PSI): 11.6 PSI	<b>Fitment Information:</b>
Inside Diameter: 38mm	Engine 620DS, 634DS, 634TCC,
Working Diameter: 55mm	645TCC
	

<b>KR-VPE3257</b>	<b>OEM:</b>
Max. Working Pressure: 1.0 BAR	
Pressure (PSI): 14.5 PSI	<b>Fitment Information:</b>
Inside Diameter:	Engine 33AWIC, 44AWI, 49AWI,
Working Diameter:	66AWI, 74AWI, 84CTA
	


<b>KR-VPE3264</b>	<b>OEM:</b>
Max. Working Pressure: 0.95 BAR	
Pressure (PSI): 13.7 PSI	<b>Fitment Information:</b>
Inside Diameter:	Engine 44CTA, 49CTA, 66ETA,
Working Diameter:	74CTA, 84CTA
	

# Standard (Hotchkiss)


<b>KR-VPE3202</b>	<b>OEM:</b>
Max. Working Pressure: 0.5 BAR	
Pressure (PSI): 7 PSI	<b>Fitment Information:</b>
Inside Diameter: 37mm	Engine 23C, 87MM
Working Diameter: 57mm	
	

<b>KR-VPE3251</b>	<b>OEM:</b>
Max. Working Pressure: 0.3 BAR	
Pressure (PSI): 4 PSI	<b>Fitment Information:</b>
Inside Diameter:	Engine 20C, 80MM, 85MM
Working Diameter:	
	

# Steyr

<b>KR-3134146R1N</b>	OEM:
Max. Working Pressure: 0.8 BAR	
Pressure (PSI): 11.6 PSI	<b>Fitment Information:</b>
Inside Diameter: 38mm	9155, 9170, 9190
Working Diameter: 5mm	
	


<b>KR-3475308M1N</b>	OEM:
Max. Working Pressure: 0.5 BAR	
Pressure (PSI): 7 PSI	<b>Fitment Information:</b>
Inside Diameter:	360 COMPACT, 370 COMPACT, 375 COMPACT, 485 COMPACT, 495 COMPACT, 955, 964, 970, 9078, 9080M, 9086, 9090M, 9094, 9100M, 9105, 9115, 9125, 9145, CVT120, 130, 150, 170, M948, M952, M958, M963, M968, M975, M9078, M9083, M9086, M9094
Working Diameter:	
	

<b>KR-4274034</b>	OEM:
Max. Working Pressure:	
Pressure (PSI):	<b>Fitment Information:</b>
Inside Diameter:	370 COMPACT, 375 COMPACT, 485 COMPACT, 495 COMPACT, 4065 COMPACT, 4075 COMPACT, 4085 COMPACT, 4095 COMPACT
Working Diameter:	
	

<b>KR-81747955N</b>	OEM: 162000530701, 81747955
Max. Working Pressure: 0.8 BAR	
Pressure (PSI): 11.6 PSI	<b>Fitment Information:</b>
Inside Diameter: 36.5mm	360 COMPACT, 370 COMPACT, 375 COMPACT, 485 COMPACT, 495 COMPACT, 9105, 9115, 9125, 9145, CVT120, 130, 150, 170
Working Diameter: 55mm	
	


<b>KR-AL56759N</b>	OEM:
Max. Working Pressure: 0.6 BAR	
Pressure (PSI):	<b>Fitment Information:</b>
Inside Diameter: 38mm	360 COMPACT, 370 COMPACT, 375 COMPACT, 485 COMPACT, 495 COMPACT
Working Diameter: 54mm	
	


# Ursus

KR-VPE3206	OEM:
Max. Working Pressure: 0.7 BAR	
Pressure (PSI): 10 PSI	<b>Fitment Information:</b>
Inside Diameter:	2802, 2812, 3502, 3512, 3514, 5312, 5314, MF231
Working Diameter:	
	


# Valtra-Valmet

<b>KR-3134146R1N</b>	OEM:
Max. Working Pressure: 0.8 BAR	
Pressure (PSI): 11.6 PSI	<b>Fitment Information:</b>
Inside Diameter: 38mm	205, 255, 305, 315, 355, 365, 405, 415, 455, 465, 555, 565, 665, 865, 6000, 6100, 6200, 6300, 6400, 6600, 6800, 6900, 8000, 8050, 8100, 8150, 8200, 8400, 8450, 8550, 8750, MEGA 8450E
Working Diameter: 55mm	
	


<b>KR-4999682N</b>	OEM:
Max. Working Pressure: 0.7 BAR	
Pressure (PSI): 10 PSI	<b>Fitment Information:</b>
Inside Diameter:	355
Working Diameter:	
	

<b>KR-81747955N</b>	OEM:
Max. Working Pressure: 0.8 BAR	
Pressure (PSI): 11.6 PSI	<b>Fitment Information:</b>
Inside Diameter: 36.5mm	465
Working Diameter: 55mm	
	

<b>KR-AL56759N</b>	OEM:
Max. Working Pressure: 0.6 BAR	
Pressure (PSI):	<b>Fitment Information:</b>
Inside Diameter: 38mm	465
Working Diameter: 54mm	
	

<b>KR-V33690710</b>	OEM: 33690710, V33690710
Max. Working Pressure:	
Pressure (PSI):	<b>Fitment Information:</b>
Inside Diameter:	A82, A83, A92, A93, N82, N92, N93, N103, N104, N113, N114, N123, N124, N134, N143, N154, N163, N174, T133, T144, T153, T154, T163, T173, T174, T183, T193, T194, T203, T213, T214, T234, T254
Working Diameter:	
	

<b>KR-VPE3257</b>	OEM: 4356380M1
Max. Working Pressure: 1.0 BAR	
Pressure (PSI): 14.5 PSI	<b>Fitment Information:</b>
Inside Diameter:	S233, S263, S293, S323, S353
Working Diameter:	
	

<b>KR-VPE3264</b>	OEM: 4296015M1
Max. Working Pressure: 0.95 BAR	
Pressure (PSI): 13.7 PSI	<b>Fitment Information:</b>
Inside Diameter:	S232, S233, S262, S263, S292, S293, S322, S323, S352, S353
Working Diameter:	
	

<b>KR-VPE3266</b>	OEM: 33057300, V33057300
Max. Working Pressure:	
Pressure (PSI):	<b>Fitment Information:</b>
Inside Diameter:	600, 700, 800, 900, 6250, 6350, 6550, 6650, 6750, 6850, 8050, 8150, 8350, 8450, 8550, 8950, A65, A75, A85, A95
Working Diameter:	
	

KR-VPE3267	OEM: 33589100, 836362504, V33589100, V836362504
Max. Working Pressure: 0.75 BAR	
Pressure (PSI): 10.8 PSI	<b>Fitment Information:</b>
Inside Diameter:	600, 700, 800, 900
Working Diameter:	
	



# Zetor

<b>KR-972501</b>	OEM: 972501
Max. Working Pressure: 0.8 BAR	
Pressure (PSI): 11.6 PSI	<b>Fitment Information:</b>
Inside Diameter: 39mm	Engine 5201D, 6201D, 7701D, Z2001, Z3001, Z4001, Z4701, Z4901, Z5001, Z5201, Z5501, Z5901, Z6001, Z6701, Z6901, Z7001, Z7201, Z8001, Z8002.1, Z8002.134, Z8401, Z8601, Z8602, Z8701
Working Diameter: 55mm	Tractor 2511, 3011, 3320, 3321, 3340, 3341, 3511, 3513, 3545, 4320, 4321, 4340, 4341, 4511, 4611, 4712, 4718, 4911, 5011, 5211, 5245, 5320, 5321, 5340, 5341, 5511, 5516, 5545, 5611, 5645, 5647, 5711, 5718, 5745, 5748, 5911, 5945, 6011, 6045, 6211, 6245, 6320, 6321, 6340, 6341, 6711, 6718, 6745, 6748, 6911, 6945, 7011, 7045, 7211, 7245, 7320T, 7321T, 7340T, 7341T, 7520, 7540, 7711, 7711T, 7745, 7745T, 8011, 8045, 8111, 8145, 8211, 8245, 8520T, 8540T, 8621T, 8641T, 9211, 9245, 9520T, 9540T, 9621T, 9641T, 10111, 10145, 10211, 10245, 10540T, 10641T, 11211, 11245, 11441T, 11741T, 12011, 12045, 12111, 12145, 12211, 12245, 14245, 16145, 16245
	

<b>KR-K906196N</b>	OEM:
Max. Working Pressure: 0.3 BAR	
Pressure (PSI): 4 PSI	<b>Fitment Information:</b>
Inside Diameter:	Engine 5201D, 6201D, 7701D, Z2001, Z3001, Z4001, Z4701, Z4901, Z5001, Z5201, Z5501, Z5901, Z6001, Z6701, Z6901, Z7001, Z7201, Z8001, Z8002.1, Z8002.134, Z8401, Z8601, Z8602, Z8701
Working Diameter:	Tractor 2511, 3011, 3511, 3513, 3545, 4511, 4611, 4712, 4718, 4911, 5011, 5211, 5245, 5511, 5516, 5545, 5611, 5645, 5647, 5711, 5718, 5745, 5748, 5911, 5945, 6011, 6045, 6211, 6245, 6711, 6718, 6745, 6748, 6911, 6945, 7011, 7045, 7211, 7245, 7711, 7745, 8011, 8045, 8111, 8145, 10111, 10145, 12011, 12045, 12111, 12145, 16145
	

<b>KR-VPE3201</b>	OEM: 951316, 951325, 972501
Max. Working Pressure: 0.3 BAR	
Pressure (PSI): 4 PSI	<b>Fitment Information:</b>
Inside Diameter:	Engine 5201D, 6201D, 7701D, Z2001, Z3001, Z4001, Z4701, Z4901, Z5001, Z5201, Z5501, Z5901, Z6001, Z6701, Z6901, Z7001, Z7201, Z8001, Z8002.1, Z8002.134, Z8401, Z8601, Z8602, Z8701
Working Diameter:	Tractor 2511, 3011, 3511, 3513, 3545, 4511, 4611, 4712, 4718, 4911, 5011, 5211, 5245, 5511, 5516, 5545, 5611, 5645, 5647, 5711, 5718, 5745, 5748, 5911, 5945, 6011, 6045, 6211, 6245, 6711, 6718, 6745, 6748, 6911, 6945, 7011, 7045, 7211, 7245, 7711, 7745, 8011, 8045, 8111, 8145, 10111, 10145, 12011, 12045, 12111, 12145, 16145
	



**WE KEEP FARMERS FARMING**